

DVR

Provision-ISR DVRs feature the advanced H.264-H265 video compression format for maximum video quality alongside minimum storage volume. Their Dynamic Hybrid function allows installers to decide how the analog channels will work according to the installation needs, making this installation totally dynamic.



SH-8100A5N-2L(MM)-V2

8CH "4 In 1" + 2CH IP Dynamic Hybrid DVR

Provision-ISR SH-8100A5N-2L(MM)-V2 is a high-quality dynamic hybrid digital video recorder obtainable in an elegant mini metal case. This technology allows users to add advanced IP cameras alongside analog ones and enjoy high-quality images and other advanced features available on IP cameras only. The recorder supports Provision-ISR Standard Video Analytics (Pixel Based).

8
CH

2
MP
LITE



2MP
lite
Resolution

4 in 1

Video
Analytics

H.265
H.264

2-Way
Audio

CoC
Control over
coax

NDAA

4 IN 1

HYBRID
DVR

AI
ENGINE

MAIN FEATURES

- Video Input: 8CH Standard BNC + 2CH IP Video Output: HDMI - FHD VGA Recording: HD Analog: 2MP lite / 1MP: Up to 12/15FPS Per Channel CVBS: 960H: Up to 25/30FPS Per Channel IP: 5MP: 25FPS Per Channel, 4MP and lower: 25/30FPS Per Channel Playback: Local: 8Ch Simultaneously Remote: 4Ch Simultaneously Audio: Input: 1CH + IPC Inputs Output: 1CH + IPC Outputs Alarm: Input: IP Cameras only Output: IP Cameras only Storage: 1 x SATA (Up to 6TB each) Network: 1 x RJ-45: 10/100Mbps PTZ Support: CoC / IP over Network Power Supply: DC12V/2A Analytics: AI by IPC: DDA1 Analytics Supported by the camera AI By DVR: AI Object detection, Line Crossing/Sterile Area (Up to 1 channel, at the expense of 4 SMD channels) Remarks: The following features are based on firmware v1.3.8 and are subject to firmware version changes.



<https://provision-isr.com>

SPECIFICATIONS

| NDAA Compliant | |
|------------------------------------|--|
| NDAA Compliant | Yes |
| General | |
| Technology | Hybrid DVR |
| Recording Modes | Schedule, Manual, Motion, Sensor, Analytics, POS |
| Format | "All in 1" Hybrid (AHD / CVI / TVI / CVBS + IP) |
| Video Input | |
| Video Input (Max Analog) | 8CH Standard BNC + 2CH IP (Over Network) |
| Video Input (Max IP) | 10CH IP (Over Network) + 0CH Standard BNC |
| 3K Input Support | No |
| Video Output | |
| Video Output | HDMI(1920x1080), VGA (1280x1024, 1024x768) |
| Dual Output | Mirrored |
| Audio | |
| Audio-In | 1CH RCA (2.0 Vp-p, 1 kΩ) (+IP Cameras) |
| Audio-Out | 1CH RCA (2.0 Vp-p, 1 kΩ) (+IP Cameras) |
| Audio Over Coax | Yes (TVI Only) |
| Two Way Audio | Yes |
| Audio Compression | G.711u |
| Events and Analytics | |
| SMD Support | Yes |
| DDA Analytics (On Analog Channels) | Yes |
| Pixel Based Analytics | Yes |
| Main Resolution and FPS | |

| | |
|-----------------------------------|---|
| IP Main Stream | 5MP: 25FPS Per Channel, 4MP and lower: 25/30FPS Per Channel |
| AHD | AHD 2MP lite / 1MP: Up to 12/15FPS Per Channel |
| TVI | 2MP lite / 1MP: Up to 12/15FPS Per Channel |
| CVI | 2MP lite / 1MP: Up to 12/15FPS Per Channel |
| CVBS Main Stream | CVBS: 960H: Up to 25/30FPS Per Channel |
| Master Stream Over Network | 4Ch |

Network (Substream) Resolution and FPS

| | |
|--------------------------------|---|
| HD Analog | 1-25/30FPS@D1 Per Channel (FPS Restricted to Master Stream FPS) |
| IP Sub Stream | 1-25/30FPS@D1 Per Channel |
| CVBS Sub Stream | 1-25/30FPS@D1 Per Channel |
| Substreams over Network | 50 (Outgoing bandwidth limit applies) |

Remote view

| | |
|-------------------------|---|
| Max Channel View | 50Ch (Limited to Outgoing Bandwidth Capacity) |
|-------------------------|---|

Video Compression

| | |
|--------------------------|----------------------|
| Video Compression | H.265 (HEVC) / H.264 |
|--------------------------|----------------------|

Record

| | |
|-----------------------|------------------|
| Recording Mode | Main Stream only |
|-----------------------|------------------|

Remote Applications

| | |
|----------------------------------|---|
| User Access | 5 Users Online with Professional Authority Management |
| Mobile App | Provision Cam2 for iOS/Android |
| PC/Mac Software | Ossia VMS Standard / Enterprise |
| Plug-in free Web-Browser | Chrome, FireFox, Safari, Edge, Opera. (All Limited to 4Ch Live View / Playback) |
| Plug-in based Web-Browser | Internet Explorer |

| Bandwidth | |
|---------------------------------|--|
| Incoming | 16Mbps |
| Outgoing | 60Mbps |
| Playback | |
| Local Playback Channels | 8Ch |
| Remote Playback Channels | 4Ch |
| Search Modes | Time-Slice, Time, Event, File Management, Smart Search |
| Backup | |
| USB | 2 USB 2.0 Port |
| Backup Format | AVI/DAT |
| Alarm | |
| Alarm-in | IP Cameras only |
| Alarm-out | IP Cameras only |
| Alarm Box Support | Yes |
| Storage | |
| HDD Max Capacity | 6TB |
| Total HDD Max Capacity | 6TB |
| Number of HDD | 1 |
| E-Sata | No |
| PTZ | |
| Connection | CoC / IP over Network |
| Supported Protocols | Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC |
| Supported Controls | Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus |

| Network | |
|------------------------------|---|
| Ethernet | 100 Mbps (RJ-45) |
| Protocols | TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP, HTTPS, FTP, SNMP, P2P, POS |
| ONVIF | Yes (For IP Channels) |
| Others | |
| Dimensions | W255xD220xH43mm |
| Power Supply | DC12V/2A |
| Operation Temperature | 0°C ~50°C |

DIMENSIONS

