

PoE Switches

Provision-ISR PoE Switches are designed to push power and data further and much stronger, ending the discouraging signal transmission loss. Our PoE series offer ultra-long distance transmission, reliable power supplies with high-voltage surge protection, and support multiple protocols, providing the installer with the highest flexibility in the design of the system and the wiring.



PoES-08120GCL+2Combo

8 Downlink 10/100/1000Mbps + 2 Uplink 10/100/1000Mbps/SFP Combo 120W PoE Switch with CCTV Mode

The "PoES-08120GCL+2Combo" is a 10*10/100/1000Mbps 8-port PoE + 2G downlink/uplink ports Ethernet switch. The switch auto-detects connected IEEE802.3af/at compliant Powered Devices (PD) and supplies power to them. The PoE objective is to deploy independent power to places with no power source and outlets. The CCTV mode allows a camera connection up to a 250m distance.



MAIN FEATURES

- PoES-08120GCL+2Combo
- PoE Ports: 8
- Downlink Ports: 8
- Uplink Ports: 2
- SFP Ports: 2(Overrides RJ45 Uplink Ports)
- Download Speed: 10/100Mbps
- Uplink Speed: 10/100Mbps
- Total Power: 120W
- Maximum Power Per Channel: 30W
- Backbone Bandwidth: 20Gbps
- Buffer Size: 1500Kbit
- MAC Address Table: 4K
- CCTV Mode: Selectable Standard/CCTV Mode
- VLAN: Disabled/Auto
- Keep Alive Feature
- Power Supply: 100-240VAC
- Power Consumption: PoE on: 130W Max. / PoE off: 10W Max.
- Dimensions: 280*180*44mm
- Weight: ~2.5Kg



<https://provision-isr.com>

SPECIFICATIONS

| Interface | |
|----------------|-----------------------------|
| Downlink Ports | 8*10/100/1000Mbps RJ45 port |
| Uplink Ports | 2 x 10/100/1000Mbps port |
| SFP Ports | 2 x 10/100/1000Mbps |

| PoE | |
|---------------------------|--|
| PoE Ports | 8 |
| Ethernet Standards | IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at |
| PoE Total Power | 120W |
| Average Power Per Channel | 15.4W |
| Maximum Power Per Channel | 30W |

| Data Processing | |
|--------------------|--------------------------------|
| Backbone Bandwidth | 20Gbps |
| Buffer Size | 1500Kbit |
| MAC Address Table | 4K |
| VLAN | 2 Auto Modes (VLAN/CCTV Modes) |

| Network Media | |
|---------------|---|
| EIA/TIA-568 | 100Ω STP (Maximum 100m) |
| 10BASE-T | 10BASE-T: UTP category 3,4,5 cable (≤100m) |
| 100BASE-TX | 100BASE-TX: UTP category 5,5e cable (≤100m) |
| 1000BASE-T | 1000BASE-T: UTP category 5,5e cable (≤100m) |
| 1000BASE-X | 1000BASE-X: MMF, SMF |

| Special | |
|-----------------|------------------------------------|
| CCTV Mode | Selectable Standard/CCTV Mode |
| Surge Protector | Different mode±2KV common mode±4KV |

PoES-08120GCL+2Combo

| | |
|------------------------------|---------------------------------------|
| Wall Bracket | No |
| Rack Bracket | No |
| K-Slot (Anti Theft) | No |
| Power | |
| Status Monitor | N/A |
| Keep Alive | Yes |
| Power Supply | 100-240VAC |
| Others | |
| Power Consumption | PoE on: 130W Max. / PoE off: 10W Max. |
| Fan | 1 |
| Dimensions | 280*180*44mm |
| Weight | ~2.5Kg |
| Operating Temperature | -5°C ~ 40 °C |